



Awaiting image in new grey colours



V-4012-F (FIXED TABLE)

SPECIFICATIONS

Throat Depth	39-3/8" (1000mm)
Work Height	12-3/8" (314)
Blade Width	1/8" thru 1" (3 thru 25mm)
Blade Length	194-7/8" (4950 mm)
Bandwheel Dimensions	17" x 1-3/4" (430 x 44mm)
Bandwheels Number	4
Wheel Tires	Easily Replacable Rubber Tires
Table Type	Fixed
Main Table Size	26-3/4" x 29" (679 x 736mm)
Auxiliary Table Size	26-3/4" x 18-7/8" (679 x 477mm)
Table Tilt	45° R, 15° L
Table Workheight	40-1/8" (1019mm)
Blade Drive Motor	4 HP
Electric Controls	Mag Motor Starters, 115 Volt Controls
Blade Speed	50-5200 fpm (15-1575 mpm)
Transmission	Totally Enclosed
Blade Welder, Grinder, Shear	1" Capacity, Standard Equipment
Dimension:	
Length	70-1/2" (1790mm)
Width	42-1/2" (1079mm)
Height	75" (1905mm)
Net Weight	2596 lbs (1180 kgs)

V-4012-H (HYDRAULIC TABLE)

SPECIFICATIONS

Throat Depth	39-3/8" (1000mm)
Work Height	12" (304mm)
Blade Width	1/8" thru 1" (3 thru 25mm)
Blade Length	194-7/8" (4950mm)
Bandwheel Dimensions	17" x 1-3/4" (430 x 44mm)
Bandwheels Number	4
Wheel Tires	Easily Replacable Rubber Tires
Table Type	Hydraulic Powered
Main Table Size	26-3/4" x 29" (679 x 736mm)
Auxiliary Table Size	26-3/4" x 18-7/8" (679 x 477mm)
Table Tilt	30° R, 15° L
Table Workheight	40-1/8" (1019mm)
Blade Drive Motor	4 HP
Electric Controls	Mag Motor Starters, 115 Volt Controls
Blade Speed	50-5200 fpm (15-1575 mpm)
Transmission	Totally Enclosed
Blade Welder, Grinder, Shear	1" Capacity, Standard Equipment
Table Stroke	13" (330mm)
Dimension:	
Length	70-1/2" (1790mm)
Width	44-7/8" (1138mm)
Height	75" (1905mm)
Net Weight	2750 lbs (1250 kgs)

Addison Jubilee



All Machines Fitted with Safety Brake Motor

Addison Saws Ltd
 Crackley Way
 Peartree Lane Ind Est
 Dudley, West Midlands
 DY2 0UW
 01384 456333



V-2012-F (FIXED TABLE)

SPECIFICATIONS	
Throat Depth	20" (500mm)
Work Height	12-3/4" (320mm)
Blade Width	1/8" thru 1" (3 thru 25mm)
Blade Length	161-3/8" (4100 mm)
Bandwheel Dimensions	20-1/2" x 1-3/4" (520 x 44mm)
Bandwheels Number	2
Wheel Tires	Easily Replacable Rubber Tires
Table Type	Fixed
Main Table Size	26-3/4" x 29" (679 x 736mm)
Table Tilt	45° R, 15° L
Table Workheight	40-1/8" (1019)
Blade Drive Motor	3 HP
Electric Controls	Mag Motor Starters, 115 Volt Controls
Blade Speed	50-5200 fpm (15-1575 mpm)
Transmission	Totally Enclosed
Blade Welder, Grinder, Shear	1" Capacity, Standard Equipment
Dimension:	
Length	51" (1295mm)
Width	41" (1041mm)
Height	81" (2057mm)
Net Weight	1716 lbs (780 kgs)



V-2812-F (FIXED TABLE)

SPECIFICATIONS	
Throat Depth	28" (700mm)
Work Height	12-3/4" (320mm)
Blade Width	1/8" thru 1" (3 thru 25mm)
Blade Length	198" (5030)
Bandwheel Dimensions	28-3/8" x 1-3/4" (720 x 44mm)
Bandwheels Number	2
Wheel Tires	Easily Replacable Rubber Tires
Table Type	Fixed
Main Table Size	26-3/4" x 29" (679 x 736mm)
Table Tilt	45° R, 15° L
Table Workheight	42" (1069mm)
Blade Drive Motor	3 HP
Electric Controls	Mag Motor Starters, 115 Volt Controls
Blade Speed	50-5200 fpm (15-1575 mpm)
Transmission	Totally Enclosed
Blade Welder, Grinder, Shear	1" Capacity, Standard Equipment
Dimension:	
Length	61-3/8" (1560mm)
Width	41" (1041mm)
Height	90-3/4" (2307mm)
Net Weight	2156 lbs (980 kgs)



V-2012-H (HYDRAULIC TABLE)

SPECIFICATIONS	
Throat Depth	20" (500mm)
Work Height	12" (304mm)
Blade Width	1/8" thru 1" (3 thru 25mm)
Blade Length	161-3/8" (4100mm)
Bandwheel Dimensions	20-1/2" x 1-3/4" (520 x 44mm)
Bandwheels Number	2
Wheel Tires	Easily Replacable Rubber Tires
Table Type	Hydraulic Powered
Main Table Size	26-3/4" x 29" (679 x 736mm)
Table Tilt	30° R, 15° L
Table Workheight	40-1/2" (1028mm)
Blade Drive Motor	3 HP
Electric Controls	Mag Motor Starters, 115 Volt Controls
Blade Speed	50-5200 fpm (15-1575 mpm)
Transmission	Totally Enclosed
Blade Welder, Grinder, Shear	1" Capacity, Standard Equipment
Table Stroke	13" (330mm)
Dimension:	
Length	51" (1295mm)
Width	44" (1117mm)
Height	81" (2057mm)
Net Weight	1870 lbs (850 kgs)

STANDARD FEATURES:

115V control circuit, motor overload and under volt protection, chevron blade guides 1/16" up to 1", blade tension, variable blade speed 50-5200 SFPM (15-1575 MPM), rip fence, chip blower, blade welder, grinder, shear & digital speed meter.

Awaiting image in new grey colours



V-2812-H (HYDRAULIC TABLE)

SPECIFICATIONS	
Throat Depth	28" (700mm)
Work Height	12" (304mm)
Blade Width	1/8" thru 1" (3 thru 25mm)
Blade Length	198" (5030mm)
Bandwheel Dimensions	28-3/8" x 1-3/4" (720 x 44mm)
Bandwheels Number	2
Wheel Tires	Easily Replacable Rubber Tires
Table Type	Hydraulic Powered
Main Table Size	26-3/4" x 29" (679 x 736mm)
Table Tilt	30° R, 15° L
Table Workheight	42" (1069mm)
Blade Drive Motor	3 HP
Electric Controls	Mag Motor Starters, 115 Volt Controls
Blade Speed	50-5200 fpm (15-1575 mpm)
Transmission	Totally Enclosed
Blade Welder, Grinder, Shear	1" Capacity, Standard Equipment
Table Stroke	13" (330mm)
Dimension:	
Length	61-3/8" (1560mm)
Width	44" (1117mm)
Height	90-3/4" (2307mm)
Net Weight	2310 lbs (1050 kgs)

Awaiting image in new grey colours